

3 Zone Security Alarm Control Panel For Residential and Commercial Applications

HA-863N

A Smart Alarm Control Panel For Office & Home Protections





FEATURES AND FUNCTIONS:

- 3 Protection Zones: Instant, Delay and 24 Hour Circuits, Designed for Residential and Small Commercial Premise
- All Protection Zones are End-of-Line Resistor Supervised, Compatible with Both N.O. and N.C. Sensors
- Simple Installation, Easy to Use, High Level of Quality and Reliability, Good for DIY and Professional Users
- Built-in Exit Delay, Entry Delay and Siren Timer
- Built-in Siren Driver and Output Relay Contacts
- Key Switch or Digital Keypad for Arm-Disarm Control

HA-863NK comes with a key switch station RKS-2L for arm-disarm control. The RKS-2L is a latch-type key switch with 2 LED indicators. Simply turn key switch to arm-disarm the system and the LEDs indicate the system status.

HA-863ND comes with a digital keypad control station DK-863C for arm-disarm control. The LED indicators on the DK-863C for indicating system status. Simply enter the digital user code to arm-disarm the system. The user code can be changed by owner.

SPECIFICATIONS:

Protection Zone : One Delay Zone, One Instant Zone (with handover function) and One 24 Hour Instant Zone,

N.C. and N.O. End-of-Line Resistor Supervised

Exit Delay
 Entry Delay
 60 Seconds Typical
 1-99 Seconds Adjustable

• Siren Duration : 30 Seconds-10 Minutes Adjustable

Output Relay
 12V DC Output Contacts at Normal and Alarm Condition N.C. Dry Contact at Normal Condition

Siren Driver : Drive Two 8-Ohm Horn Speaker Maximum, Warble Tone

Operating Voltage: 16V AC

Back-Up Power : 12V DC/1.2AH Rechargeable Lead Acid Battery (Battery not Included)

Standby Current : 32mA

Dimension : 258 x 172 x 72 mm

Net Weight : 1.8 Kg

MANUFACTURER & EXPORTER



TEL : (852) 24299719
FAX : (852) 24892411
E-MAIL : aei@aei-secucom.com
WEBSITE : http://www.aei-secucom.com

RoHS COMPLIANT